


To view online, go to: <https://www.hasco-inc.com/cable-assemblies/2-4mm-male-to-2-4mm-male-test-cable-using-hll140-low-loss-phase-stable-vs-flexure-flexible-cable-48-inches/>

LTR	DESCRIPTION	DATE	APPR.	DRAWN BY: ABC	CHECKED BY: ABC		5214 Bonsai Street • Moorpark, CA 93021 (888) 498-3242 • sales@hasco-inc.com <a href="http://www.hasco-inc.com">www.hasco-inc.com</a>		
-	RELEASE	12/16	TAC	APPROVED BY: ABC					
				THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF HASCO COMPONENTS AND SHALL NOT BE REPRODUCED, COPIED NOR USED - IN WHOLE OR IN PART - AS THE BASIS FOR THE MANUFACTURE OR SALE OF OTHER ITEMS WITHOUT THE EXPRESS, WRITTEN PERMISSION OF HASCO COMPONENTS.		MATERIALS: <b>SEE DATA SHEET</b>	CAGE CODE: OT8L4	SCALE: N/A	SIZE: A
				TOLERANCES - UNLESS OTHERWISE NOTED:  ALL DIMS IN MILLIMETERS 1 PLACE ±0.20    ANGLE ±1.0° 2 PLACE ±0.10		FINISHES: <b>SEE DATA SHEET</b>	PART NO./DRAWING NO. <b>HLL140M-24P-24P-48</b>		REV: -
THIS DRAWING IS A CONTROLLED DOCUMENT									