



NOTES:

- 1.ELECTRICAL:
 - 1.1 IMPEDANCE: 50Ω
 - 1.2 INSULATION RESISTANCE:5000MΩ MIN
 - 1.3 FREQUENCY RANGE: DC~18GHZ
 - 1.4 DIELECTRIC WITHSTANDING VOLTAGE: 1000V MAX AT SEA LEVEL
 - 1.5 VSWR≤1.35:1@DC-18GHZ
 - 1.6 INSERTION LOSS: ≤0.7dB@18GHZ
- 2.ENVIRONMENTAL:

TEMPERATURE RANGE: -55° to +85°
3. CONNECTOR MATERIAL AND FINISH:

BODY: STAINLESS STEEL TYPE 303, PASSIVATE
 NUT: STAINLESS STEEL TYPE 303, PASSIVATE
 CENTER CONTACT: BERYLLIUM COPPER
 , GOLD PLATING
 DIELECTRIC: PTFE, N/A

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN DWP 25/04/2013	HASCO HyTech Associates Sales Company, Inc	
DIMENSIONS INCHES	TOLERANCES UNLESS OTHERWISE SPECIFIED	CHK	NAME HULL320 @ Series	
	0 PLC .0005 1 PLC .0010 2 PLC .0015 3 PLC .0020 4 PLC .0030 ANGLES ±1°	APVD	PRODUCT SPEC 18GHz Ultra Low Loss Flexible Cable Assemblies with Excellent Phase Stability vs. Flexure & Temperature	
MATERIAL SEE TABLE	FINISH SEE TABLE	APPLICATION SPEC	SIZE A3	CAGE CODE 0TBL4
		WEIGHT	DRAWING NO HULL320-S1-S1-18	
		CUSTOMER DRAWING		SCALE 1:1
		SHEET 1	OF 1	RVE 1